

BLANK PAGE





Indian Standard

SPECIFICATION FOR COACH SCREWS

(First Revision)

- 1. Scope Covers the requirements of hexagon head coach screws (hexagon head wood screws).
- 2. Dimensions
- 2.1 As given in Table 1.
- 2.2 The preferred length and screw number combinations shall be as given in Table 2.
- 3. Tolerances As given in Fig. 1.




FIG. 1 TOLERANCES ON HEXAGON HEAD COACH SCREW

- 4. Material As given in IS: 451-1972 'Technical supply conditions for wood screws (second revision)'.
- 5. General Requirements In regard to the requirements not covered in this standard, it shall conform to the requirements of IS: 451-1972.
- 6. Designation Shall be designated by the name, screw number, length, number of this standard and material.

Example:

A hexagon head coach screw of screw No. 10, length 30 mm and made of steel, shall be designated as:

Coach Screw No. 10×30 IS: 1120 Steel

- 7. Finish As given in IS: 451-1972.
- 8. Inspection and Acceptance As given in IS: 451-1972.
- 9. Packing As given in IS: 451-1972.
- 10. Marking
- 10.1 As given in IS: 451-1972.
- 10.2 ISI Certification Marking Details available with the Indian Standards Institution.

Adopted 30 January 1975


1975, ISI



TABLE 1 DIMENSIONS FOR HEXAGON HEAD COACH SCREWS

(Clause 2.1)

All dimensions in millimetres.



Size No. Screw Designa-	Diameter of Unthreaded Shank d		Pitch	Min	s h14 ≤ 19 s h15 > 19		k js16 < 10 js17 > 10			r Max		
tion	Nom	Max	Min			Nom	Max	Min	Nom	Max	Min	
10	4.88	5.00	4.72	2.15	8.63	8	8.00	7:64	3.2	3.88	3.12	0.6
. 14	6.30	6.43	6.05	2.82	10.89	10	10.00	9.64	4	4.38	4.62	0.6
18	7·72	7.85	. 7:47	3.39	14:20	13	13.00	12:57	5.2	5.88	5·12	0.6
24	9.86	9.98	9.00	4.53	18·72	17	17.00	16:57	7	7:45	6.55	0.6
28	11.28	11:40	11.02	4 [.] 62	20.88	19	19.00	18:48	8	8.45	7:55	1
32	12.70	12.83	12:45	5.08	26.17	24	24.00	23.16	10	10.75	9.25	1

TABLE 2 PREFERRED LENGTH — SCREW NUMBER COMBINATIONS FOR HEXAGON HEAD COACH SCREWS

(Clause 2.2)

All dimensions in millimetres.

1	SCREW NUMBER							
js 17	10	14	18	24	28	32		
20								
25								
30								
35								
40			,					
45								
50								
55								
60								
65								
70								
75								
80								
85								
90								
100								
110								
120								
130								
140						-		
150								
160								
170								
180								
190					+			
200								

Note — Preferred lengths are between the bold stepped lines.

IS: 1120 - 1975

EXPLANATORY NOTE

This standard was originally published in 1957. In the present revision, reference has been made to IS: 451-1972 regarding material, finish, packing, inspection, acceptance and marking. The preferred length and screw number combinations have also been tabulated. This standard is one of the series of Indian Standards being prepared on wood screws. Other standards belonging to this series are:

IS: 451-1972 Technical supply conditions for wood screws (second revision)

1S: 6736-1972 Specification for slotted raised countersunk head wood screws

IS: 6739-1972 Specification for slotted round head wood screws

IS: 6760-1972 Specification for slotted countersunk head wood screws.

The sizes of wood screws incorporated in the above standards are based on the size of wire gauge. Metric dimensions of these sizes are also given in the individual standards.