

# **BLANK PAGE**



## AMENDMENT NO. 1 MAY 1996 TO IS 7041: 1993 SPECIFICATION FOR CARPENTERS' PLAIN BRACE

(Page 2, clause 4) — Substitute 'IS 7125: 1974' for 'IS 7025 -'.

(PE 07)


Reprography Unit, BIS, New Delhi, India



### Indian Standard

# SPECIFICATION FOR CARPENTERS' PLAIN BRACE

- 1. Scope Covers the requirement for carpenters' plain brace.
- 2. Dimensions




All dimensions in millimetres.

Nominal Size (2×A)	A ± 2	В	C +3 -0	D +3 -0	E	F
125	62·5	12	110	125	14	24
200	100	12	115	130	14	24
250	125	12	130	150	14	24
300	150	12	145	160	14	24
350	175	12	145	170	16	26

Adopted 30 October 1973

@ January 1974, ISI

Same to Mary of Lines.



#### IS: 7041 - 1973

- 2.1 Tolerances on untoleranced dimensions shall be in accordance with the best prevalent manufacturing practice.
- 2.2 The nose shall be so designed as to accept square taper tang of bits (see IS: 6891-1973 Specification for carpenters' auger bits).
- 3. Designation A carpenter's plain brace of nominal size 300 mm shall be designated as:

Brace 300, IS: 7041

- 4. Material and Other Requirements According to IS: 7025- 'Technical supply conditions for carpenters' braces'.
- 5. Marking Braces shall be marked with nominal size, manufacturer's name, initials or recognized trade-mark and the year of manufacture.
- 5.1 ISI Certification Marking Details available with the Indian Standards Institution, New Delhi 110001.

### **EXPLANATORY NOTE**

While preparing this standard assistance has been derived from BS 1978:1965 'Bit braces' issued by British Standards Institution and the Information supplied by Chief Inspectorate of General Stores, Kanpur.