

BLANK PAGE






Indian Standard


SPECIFICATION FOR WASHERS FOR CORRUGATED SHEET ROOFING

- 1. Scope Covers the requirements for washers for corrugated sheet roofing.
- 2. Types The following types of washers are covered:
 - a) Bituminous felt washers,
 - b) Steel washers, and
 - c) Lead washers.
- 3. Dimensions Dimensions of washers for corrugated sheet roofing shall be as given in Tables 1, 2 and 3.

TABLE 1 DIMENSIONS FOR BITUMINOUS FELT WASHERS

All dimensions in millimetres.





TYPE A

TYPE B

Nominal Size, d ₁ t		D	s	Suitable Bolt Size
7	1:6	25	36	M 6
10	1.6	30	36	M8
12	1.6	30	36	M10
j			l	1

4. Grade — Washers shall conform to ordinary grade as specified in IS: 5369-1975 'General requirements for plain washers and lock washers (*first revision*)'.

5. Material

- 5.1 Steel washers shall be made from any suitable low carbon steel.
- **5.2** Lead washers shall be made from lead sheets as specified in IS: 405-1961 'Specification for lead sheet (revised)'.
- 6. Designation Designation of washers shall be as given in Table 4.
- 7. Sampling The method of sampling and acceptance criteria shall be in accordance with IS: 6821-1973 'Methods for sampling non-threaded fasteners'.
- 8. General Requirements
- 8.1 Steel washers for corrugated roofing shall be galvanized by hot dipping as specified in IS: 5358-1969 'Specification for hot-dip galvanized coatings on fasteners'.

Adopted 21 July 1978

© December 1978, ISI






TABLE 2 DIMENSIONS FOR STEEL WASHERS

(C/ause 3)

All dimensions n millimetres.



TYPE C

TYPE D


Φď

Nominal Size, d ₁	t	t ₁	D	D ₁	D ₁	h	s	Suitable Bolt Size
7	1.60	0.80	12	25	35	10	36	M6
10	1.69	0.80	16	25	35	10	36	M 8
12	1.60	0.80	22	25	35	10	36	M10

TABLE 3 DIMENSIONS FOR LEAD WASHERS

(Clause 3)

All dimensions in millimetres.



TYPE A

TYPE B

Nominal Size, d_1	ŧ	D	D ₁	h	Suitable Bolt Size
7	1.6	25	20	10	M6
10	1.6	25	25	10	MB
12	1'6	25	30	10	M10

IS: 8869 - 1978

TABLE 4 DESIGNATION SYSTEM FOR WASHERS

(Clause 6)

Name of Washer and Type	Nominal Size	Designation
Bituminous felt washer, Type A	7	Bituminous Felt Washer A7 IS: 8869
Steel washer, Type D	10	Steel Washer D10 — IS: 8869
Lead washer, Type B	12	Lead Washer B12 — IS: 8869

8.2 Bituminous felt washers shall be suitably impregnated. These washers when heated and maintained at a temperature of 75 \pm 1°C for 1 hour shall not get separated and flow out.

9. ISI Certification Marking — Details available with the Indian Standards Institution.

EXPLANATORY NOTE

Subsequent to the decision to revise IS: 730-1966 'Specification for fasteners for corrugated sheet roofing (revised)' splitting into three standards, this standard has been prepared on washers. Requirements of hook bolts and mushroom head bolts are being covered in separate Indian Standards.

In this standard washers suitable for bolt size M5 have not been covered.

This standard has been brought in line with BS 1494: Part I: 1964 'Fixing accessories for building purposes' issued by British Standards Institution.