

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”


IS 3443 (1980): Crane rail sections - [CED 7: Structural Engineering and structural sections]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS : 3443 - 1980
(Reaffirmed 1999)

Indian Standard
SPECIFICATION FOR
CRANE RAIL SECTIONS
(*First Revision*)

Fifth Reprint JULY 2001)

UDC 669.14-424:621.873

Copyright 1981

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

SPECIFICATION FOR CRANE RAIL SECTIONS

(First Revision)

Structural Sections Sectional Committee, SMDC 6

<i>Chairman</i>	<i>Representing</i>
SHRI M. DHAR	Kamani Engineering Corporation Ltd, Bombay
<i>Members</i>	
SHRI S. BANERJEE	Steel Re-Rolling Mills Association of India, Calcutta
SHRI N. BHATTACHARYA	Garden Reach Shipbuilder and Engineers Ltd, Calcutta
SHRI N. S. CHATTREE	Steel Authority of India Ltd, Bhilai Steel Plant, Bhilai
SHRI V. MUKUNDAN (<i>Alternate</i>)	
SHRI B. B. CHAKRAVERTY	Suprintendence Co of India (Pvt) Ltd, Calcutta
SHRI A. K. SHOME (<i>Alternate</i>)	
SHRI D. S. DEBBI	M. N. Dastur & Co Pvt Ltd, Calcutta
SHRI D. GADH	Tata Iron and Steel Co Ltd, Jamshedpur
SHRI S. K. MAHAPATRA (<i>Alternate</i>)	
SHRI S. B. GUPTA	Inspection Wing, Directorate General of Supplies and Disposals, New Delhi
SHRI P. C. MUSTAFI (<i>Alternate</i>)	
SHRI M. P. JASUJA	Steel Authority of India Ltd, Research and Development Centre for Iron and Steel, Ranchi
JOINT DIRECTOR STANDARDS (WAGON I), RDSO	Ministry of Railways
JOINT DIRECTOR STANDARDS (B & S), RDSO (<i>Alternate</i>)	
SHRI OM KISHORE	EMC Projects Pvt Ltd, Calcutta
SHRI S. N. SINGH (<i>Alternate</i>)	
SHRI P. LAXMINARAYANA	Hindustan Shipyard Ltd, Vishakhapatnam
SHRI V. A. S. NARAYANA RAO (<i>Alternate</i>)	
SHRI S. K. MITRA	Indian Iron & Steel Co Ltd, Burnpur
SHRI S. DUTTA (<i>Alternate</i>)	
SHRI P. K. MUKHERJEE	The Braithwaite and Co Ltd, Calcutta
SHRI AMIT KUMAR BHATTACHARYA (<i>Alternate</i>)	

(Continued on page 2)

© Copyright 1961

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act (XIV of 1957)* and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

<i>Members</i>	<i>Representing</i>
SHRI M. V. NAGESHAJAH	Metallurgical & Engineering Consultants (India; Ltd, Ranchi
SHRI KAMMAL PRAKASHI (<i>Alternate</i>)	
SHRI D. B. NAIK	Engineer-in-Chief's Branch, Army Headquarters
MAJ G. S. SONDH (<i>Alternate</i>)	
SHRI P. V. NAIK	Richardson and Cruddas Ltd, Bombay
SHRI P. S. RANGAVITTALAN	Iron & Steel Control, Calcutta
BRJG L. V. RAMAKRISHNA	Institution of Engineers (India), Calcutta
SHRI S. ROY	Steel Authority of India Ltd, Bokaro Steel Plant, Bokaro
SHRI K. V. RAO (<i>Alternate</i>)	
SHRI S. K. SADHU	Jessop & Co Ltd, Calcutta
SHRI S. C. CHAKRABARTI (<i>Alternate</i>)	
SHRI M. C. SARANGDHAR	Stup Consultants Ltd, Bombay
SHRI M. K. CHATTERJEE (<i>Alternate</i>)	
SHRI D. SRINIVASAN	Joint Plant Committee, Calcutta
SHRI B. P. GHOSH (<i>Alternate</i>)	
SHRI K. S. SRINIVASAN	National Buildings Organization, New Delhi
SHRI A. K. LAL (<i>Alternate</i>)	
SHRI SUBRATA ROY	Steel Authority of India Ltd, Rourkela Steel Plant, Rourkela
SHRI V. P. AGARWAL (<i>Alternate</i>)	
SHRI K. SURYANARAYANAN	Indian Aluminium Co Ltd, Calcutta
SHRI R. K. MEHTA (<i>Alternate</i>)	
SHRI D. THIRUVENKADAM	Tube Investments of India Ltd, Madras
SHRI M. SANKARAN (<i>Alternate</i>)	
SHRI C. R. RAMA RAO, Director (Struc & Met)	Director General, ISI (<i>Ex-officio Member</i>)

Secretary

SHRI M. S. NAGARAJ
Deputy Director (Struc & Met), ISI

Panel for Crane Rail Sections, SMDC 6 : P4

<i>Convener</i>	
SHRI D. GADH	The Tata Iron & Steel Co Ltd, Jamshedpur
<i>Members</i>	
SHRI J. L. AGGARWAL	Cranes and Allied Appliances Sectional Committee, SMDC 26, ISI
SHRI P. G. BARDHAN	Braithwaite & Co Ltd, Calcutta
SHRI A. K. BANERJEE CHOUDHURY	Cranes and Allied Appliances Sectional Committee, SMDC 26, ISI
SHRI D. S. DEBBI	M. N. Dastur & Co Pvt Ltd, Calcutta

(Continued on page 16)

AMENDMENT NO. 1 OCTOBER 1983
TO
IS:3443-1980 SPECIFICATION FOR CRANE RAIL
SECTIONS

(First Revision)

Alterations

*(Page 11, Fig.3, dimension) - Substitute
'13.89' for '19.89' and '20.64' for '2.84'*

*(Page 11, Fig.4, dimension) - Substitute 'R8'
for 'R23.8'*

Indian Standard

SPECIFICATION FOR CRANE RAIL SECTIONS (*First Revision*)

0. FOREWORD

0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 4 June 1980, after the draft finalized by the Structural Sections Sectional Committee had been approved by the Structural and Metals Division Council.

0.2 This standard was first published in 1966. In this revision the range of rail sizes has been enlarged to include some of the sections commonly used in the industry.

0.3 A supplementary list of rail sections covering the 125 kg/m rail (earlier designated as CR 140) a few non-metric railway rails and some non-metric and metric crane rails which are in regular use is given in Appendix A.

0.4 In the formulation of this standard assistance has been derived from:
IRS-T12-64 Flat bottom railway rails, Ministry of Railways, Government of India.

GOST 4121-76 Crane rails gosudarstvennyj komitet standartov, Meri Izmeritel'nyh Priborov SSSR (USSR).

0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS : 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard lays down the dimensions, shape and other requirements of crane rail sections.

*Rules for rounding off numerical values (revised).

2. GENERAL REQUIREMENTS FOR THE SUPPLY OF MATERIAL

2.1 General requirements relating to supply of material shall be as laid down in IS : 1387-1967*.

3. DESIGNATION

3.1 Crane rail sections conforming to this standard shall be designated by the letters ISCR followed by the head width of the rail section in millimetres. However, the crane rail sections covered in Appendix A shall be designated by the weight in kg/m.

3.2 For shop marking and drawing office purposes, abbreviated reference symbol CR instead of ISCR may be permitted provided specific understanding exists between the producer, drawing office and fabricator.

4. CHEMICAL COMPOSITION

4.1 The material when analysed in accordance with the appropriate part of IS : 228† and its relevant parts, shall have any of the chemical compositions on the finished product given in Table 1. The location of sample for chemical analysis shall be as shown in Fig. 1.

TABLE 1 CHEMICAL COMPOSITION, PERCENT

DESIGNATION ACCORDING TO IS : 1762 (Part I)-1974*		C	Mn	Si	S	P
NEW	OLD				Max	Max
55C11	C55Mn1	0.50-0.60	0.95-1.25	0.05-0.30	0.060	0.060
50C12	C50Mn1	0.40-0.60	0.90-1.45	0.03-0.30	0.060	0.060

*Code of designation of steel: Part I Based on letter symbols (first revision).

5. TENSILE PROPERTIES

5.1 The tensile test specimen shall be located as shown in Fig. 1 when tested in accordance with IS : 1608-1972‡, the steel shall have a minimum tensile strength of 710 MPa (72 kgf/mm²), with a minimum elongation of 14 percent on a gauge length of $5.65\sqrt{S_0}$ where S_0 is the area of cross section of the specimen in the gauge length.

*General requirements for the supply of metallurgical materials (first revision).

†Methods of chemical analysis of steels (second revision being issued in parts).

‡Methods for tensile testing of steel products (first revision).




FIG. 1 LOCATION OF SAMPLE FOR CHEMICAL ANALYSIS AND TENSILE TESTING

6. HARDNESS

6.1 The hardness of the rail head when tested in accordance with IS : 1500-1968* shall be not less than 200 HB.

7. SAMPLING

7.1 The number of samples to be tested for chemical analysis, tensile properties and hardness shall be one for every 100 tonnes or part thereof subject to a minimum of one specimen per cast.

8. DIMENSIONS, TOLERANCES AND SECTIONAL PROPERTIES

8.1 The dimensions of crane rail sections shall be as given in Table 2. Calculated sectional properties based on these dimensions are given in Table 3.


8.2 The tolerances on various dimensions of crane rail sections shall be as given in Table 4.

8.3 The dimensions of some of the rail sections commonly used in the country are covered in Appendix A along with relevant tolerances and sectional properties.

*Method for Brinell hardness test for steel (first revision).

TABLE 2 DIMENSIONS OF CRANE RAILS

(Clause 8.1)



DENO- NATION	DIMENSIONS, mm															
	A	B	C	D	E	F	G	H	R ₁	R ₂	R ₃	R ₄	R ₅	R ₆	R ₇	
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	
ISCR 50	90	90	55	50	25	20	20	9.70	300	26	18	6	6	5	1.5	
ISCR 60	105	105	65	60	27.5	24	22	9.82	350	32	20	6	6	5	1.5	
ISCR 80	130	130	87	80	35	32	26	9.75	400	44	26	8	8	6	1.5	
ISCR100	150	150	108	100	40	38	30	11.2	450	50	30	8	8	8	2	
ISCR120	170	170	129	120	45	44	35	15.3	500	56	34	8	8	8	2	
ISCR140	170	170	150	140	50	60	40	20.6	700	60	40	10	10	10	3	

9. FREEDOM FROM DEFECTS

9.1 The rails should be reasonably free from twist and the camber shall not exceed 0.2 percent of the length.

9.2 The asymmetry of the rail cross section with respect to the vertical axis shall not exceed 2 mm and 0.6 mm in the rail flange and head respectively.

TABLE 3 SECTIONAL PROPERTIES OF CRANE RAIL SECTIONS
(Class 8.1)

DENOMINATION	CROSS SECTIONAL AREA	WEIGHT*	PORTIONS OF CENTRE OF GRAVITY		MOMENTS OF INERTIA		SECTION MODULI		
			e_x	e_y	I_x	I_y	$Z_{x1} = I_{x1}/e_x$	$Z_{x2} = I_{x2}/e_x$	$Z_y = I_y/b_s$
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)
	cm ²	kg/m	cm	cm	cm ⁴	cm ⁴	cm ³	cm ³	cm ³
CR 50	38.0	29.8	4.32	4.68	337.5	111.4	82.8	76.4	24.8
CR 60	51.0	40.0	4.83	5.67	654.6	195.9	136	116	37
CR 80	81.8	64.2	6.47	6.53	1 524	468.6	233	233	72.1
CR100	113	89.0	7.63	7.37	2 806	920	368	381	123
CR120	151	118	8.69	8.31	4 794	1 672	552	577	197
CR140	187	147	8.75	8.25	5 528	2 609	632	670	307

*On the basis of density of steel=7.85 kg/dm³.

TABLE 4 TOLERANCES
(Class 8.2)

All dimensions in millimetres.

DIMENSION	RAIL SECTION		
	ISCR 50, 60 and 80	ISCR 100	ISCR 120 and 140
Head width	±2	±2	+2 -3
Thickness of head	±1	±1	±1
Flange width	±2	+2 -3	+2 -4
Web thickness	±2	±2	±2
Height	±1	±1.5	±2
Length	+100 0	+100 0	+100 0
Weight	+3 -2 percent	+3 -2 percent	+3 -2 percent

10. MARKING

10.1 Crane rail sections shall be marked with the following details:

- Manufacturer's identification mark, and
- Designation (see 3.1 and Tables 2 and 3).

10.1.1 The material may also be marked with the ISI Certification Mark.

NOTE.— The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

APPENDIX A*(Clauses 0.3 and 8.3)***SUPPLEMENTARY LIST OF CRANE RAIL SECTIONS**


A-1. The dimensions of 22, 30, 32, 43, 45, 52A, 52B, 57, 67, 74, 75, 101 and 125 kg/m crane rail sections are given in Table 6 and Fig. 2 to 8. The sectional properties are given in Table 5.

TABLE 5 SECTIONAL PROPERTIES OF NON-METRIC CRANE RAIL SECTIONS

DESIGNATION	AREA	WEIGHT	MOMENT OF INERTIA	SECTION MODULUS	RADIUS OF GYRATION	DISTANCE OF NEUTRAL AXIS	REFERENCE TO FIG./TABLE
			I_{xx}	Z_{xx}	r_{xx}	e_x	
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
kg/m	cm ²	kg/m	cm ⁴	cm ³	cm	cm	
22	28.3	22.2	91	27.5	1.79	3.31	Table 6
30	38.0	29.8	681	116	4.23	5.87	Fig. 2
32	40.7	32.0	182	46.9	2.11	3.88	Table 6
43	55.4	43.5	327	73.7	2.42	4.44	Table 6
45	56.7	44.5	1 584	212	5.30	7.48	Fig. 3
52-1	66.0	52.1	1 204	199	4.27	6.64	Fig. 4
52-2	66.5	52.2	1 270	198	4.37	6.43	Fig. 5
57	72.1	56.6	543	109	2.74	5.00	Table 6
67	85.4	67.0	2 705	311	5.63	8.70	Fig. 6
74	94.8	74.4	895	170	3.07	5.21	Fig. 7
75	95.6	75.2	888	170	3.03	5.21	Table 6
101	129	101	1 420	249	3.32	5.70	Table 6
125	138	122	3 745	492	4.87	7.60	Fig. 8

**TABLE 6 DIMENSIONS OF 22, 32, 43, 57, 75 AND 101 KG/M
CRANE RAIL SECTIONS**

(Clause A-1)



DESIGNATION	DIMENSIONS, mm														
	D	B	b	F	f ₁	f ₂	H	A	E	h	r ₁	r ₂	r ₃	r ₄	r ₅
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)
22	45	125	54	24	14.5	11	8	55±1	24	20	4	3	4	5	4
32	55	150	66	31	17.5	12.5	9	65±1	28.5	25	5	5	5	6	5
43	65	175	78	38	20	14	10	75±1	34	30	6	5	5	6	5
57	75	200	90	45	22	15.4	11	85±1	39.5	35	8	6	6	8	6
75	100	200	100	60	23	16.5	12	95±1.5	45.5	40	10	6	6	8	6
101	120	220	120	72	30	20	14	105±1.5	55.5	47.5	10	6	10	10	6

A-2. TOLERANCES


A-2.1 The tolerances on the dimensions and weight of crane rails covered in this appendix shall be as given in Table 7.

TABLE 7 TOLERANCES

(Class A-2.1)


All dimensions in millimetres.

DIMENSIONS	RAIL SECTION				
	22, 32, 43 and 57 kg/m	30, 45 kg/m	75 kg/m	52.1, 52.2, 67, 74 and 125 kg/m	101 kg/m
Head width	±2	+0.80 -0.40	±2	+2 -3	+2 -3
Thickness of head	±1	±1	±1	±1	±1
Flange width	±2	±0.80	+2 -3	+2 -4	+2 -4
Web thickness	±2	+0.80 -0.40	±2	±2	±2
Height	±1	+0.80 -0.40	±1.5	±2	±2
Length	+100 0	+100 0	+100 0	+100 0	+100 0
Weight	+3 -2 percent	+3 -2 percent	+3 -2 percent	+3 -2 percent	+3 -2




All dimensions in millimetres.

FIG. 2 30 kg/m CRANE RAIL SECTION




All dimensions in millimetres.

FIG. 5 52.2 kg/m CRANE RAIL SECTION




All dimensions in millimetres.

FIG. 6 67 kg/m CRANE RAIL SECTION



All dimensions in millimetres.

FIG. 7 74 kg/m CRANE RAIL SECTION



All dimensions in millimetres.

FIG. 8 125 kg/m CRANE RAIL SECTION

IS : 3443 - 1980

(Continued from page 2)

Members

SHRI S. R. JAINWAL

SHRI T. P. BULANI (*Alternate*)

SHRI K. K. MANGAL

SHRI P. VIJWAKARMA (*Alternate*)

SHRI B. P. MATTI

SHRI S. K. MITRA

SHRI R. N. SINHA

Representing

Steel Authority of India Ltd, Rourkela Steel Plant,
Rourkela

Tata Iron & Steel Co Ltd, Jamshedpur

Metallurgical and Engineering Consultants (India)
Ltd, Ranchi

Indian Iron & Steel Co Ltd, Burnpur

Cranes and Allied Appliances Sectional Committee,
SMDC 26, ISI

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 323 0131, 323 3375, 323 9402 Fax :+ 91 011 3234062, 3239399, 3239382

E - mail : bis@vsnl.com. Website : <http://www.bis.org.in>

Central Laboratory:

Plot No. 20/9, Site IV, Sahibabad Industrial Area, Sahibabad 201010

Telephone

477 00 32

Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002 323 76 17

*Eastern : 1/14 CIT Scheme VII, V.I.P. Road, Kankurgachi, CALCUTTA 700054 337 86 62

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022 60 38 43

Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600113 254 13 15

†Western : Manakalaya, E9, MIDC, Behind Marol Telephone Exchange, Andheri (East), MUMBAI 400093 832 92 95

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001 550 13 48

Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road, BANGALORE 560058 839 49 55

Commercial-cum-Office Complex, Opp. Dushera Maidan, E-5 Area Colony, Bittan Market, BHOPAL 462016 72 34 52

62/63, Ganga Nagar, Unit VI, BHUBANESWAR 751001 40 36 27

5th Floor, Kovai Towers, 44 Bala Sundaram Road, COIMBATORE 641018 21 88 35

Plot No. 58, Neelam Bata Road, NIT, FARIDABAD 121001 542 82 61

Savitri Complex, 116 G.T. Road, GHAZIABAD 201001 471 19 98

53/5 Ward No.29, R.G. Barua Road, 5th By-lane, Apurba Sinha Path, GUWAHATI 781003 54 11 37

5-8-56C, L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001 320 10 84

E-52, Chitrangan Marg, C- Scheme, JAIPUR 302001 37 38 79

117/418 B, Sarvodaya Nagar, KANPUR 208005 21 68 76

Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, LUCKNOW 226001 21 89 23

NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010 52 51 71

Mahabir Bhawan, 1st Floor, Ropar Road, NALAGARH 174101 2 14 51

Patliputra Industrial Estate, PATNA 800013 26 28 08

First Floor, Plot Nos. 657-660, Market Yard, Gultekdi, PUNE 411037 426 86 59

'Sahajanand House' 3rd Floor, Bhaktinagar Circle, 80 Feet Road, RAJKOT 360002 37 82 51

T.C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPURAM 695034 32 21 04

*Sales Office is at 5 Chowringhee Approach, P.O. Princep Street, CALCUTTA 700072 237 10 85

†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007 309 65 28