

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 4122 (1967): Method of test for surface softening of natural building stones by exposure to acidic atmospheres [CED 6: Stones]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS : 4122 - 1967

Indian Standard
METHOD OF TEST FOR
SURFACE SOFTENING OF NATURAL
BUILDING STONES BY EXPOSURE TO
ACIDIC ATMOSPHERES

(Second Reprint APRIL 1990)

UDC 691.2:[551.3.053]

© Copyright 1967

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

METHOD OF TEST FOR SURFACE SOFTENING OF NATURAL BUILDING STONES BY EXPOSURE TO ACIDIC ATMOSPHERES

Stones Sectional Committee, BDC 6

Chairman

SHRI O. MUTHAICHEN

Representing

Central Public Works Department

Members

SHRI G. C. DAS	National Test House, Calcutta
DEPUTY CHIEF ENGINEER, CENTRAL RAILWAY	Ministry of Railways
DEPUTY CHIEF ENGINEER (DESIGNS)	Public Works Department, Government of Mysore
DIRECTOR COST CONTROL	Central Water & Power Commission
SHRI M. K. GUPTA	Himalayan Tiles and Marble Private Limited, Bombay
SHRI S. K. JOGLEKAR	Central Public Works Department
SHRI N. KABRA	Makrana Marble & Stone Co, Makrana
SHRI V. S. KAMAT	The Hindustan Construction Co Ltd, Bombay
SHRI S. KRISHNA IYER	Builders' Association of India, Bombay
SHRI V. S. KRISHNASWAMY	Geological Survey of India, Calcutta
SHRI B. D. MATHUR	Public Works Department, Government of Rajasthan
SHRI V. R. BHATNAGAR (Alternate)	
SHRI T. R. MEHANDRU	Institution of Engineers (India), Calcutta
SHRI G. S. MEHROTRA	Central Building Research Institute (CSIR), Roorkee
SHRI D. L. MOTWANI	Ministry of Transport and Shipping (Roads Wing)
SHRI PREM SWARUP	Directorate of Geology and Mining, Government of Uttar Pradesh
SHRI A. K. AGARWAL (Alternate)	
SHRI RABINDER SINGH	National Buildings Organization, New Delhi
DR A. V. R. RAO (Alternate)	
SHRI SATJIT SINGH	Dholpur Stone Co, Baruli
SHRI M. L. SEFHI	Directorate of Mines and Geology, Government of Rajasthan
SHRI Y. N. DAVE (Alternate)	
SHRI J. S. SHAH	Associated Stones Industries (Kota) Ltd, Ramganjmandi (Rajasthan)

(Continued on page 2)

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

(Continued from page 1)

Members

SUPERINTENDENT
SHRI D. C. MITTRA (Alternate)
SUPERINTENDING ENGINEER
(DESIGNS)
SUPERINTENDING ENGINEER
(R & B)
SHRI M. V. YOGI
SHRI R. NAGARAJAN,
Director (Civ Engg)

Representing

Bisra Stone Lime Co Ltd, Birmiltrapur
Public Works Department, Government of Madras
Public Works Department, Government of Andhra
Pradesh
Engineer-in-Chief's Branch, Army Headquarters
Director General, ISI (Ex-officio Member)

Secretary

SHRI K. M. MATHUR
Assistant Director (Civ Engg), ISI

Indian Standard

METHOD OF TEST FOR

SURFACE SOFTENING OF NATURAL

BUILDING STONES BY EXPOSURE TO

ACIDIC ATMOSPHERES

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 16 May 1967, after* the draft finalized by the Stones Sectional Committee had been approved by the Civil Engineering Division Council.

0.2 Several types of natural building stones show rapid deterioration when affected by atmospheric gases like carbon dioxide, sulphur dioxide and sulphur trioxide, which form sulphuric acid with the humid air that occurs in industrial centres and sea coasts. For the selection of the proper type of stone for use in such exposed areas, it is necessary to know the resistance of stone against surface softening by action of acids. This standard lays down the method of test for this purpose.

0.3 In the formulation of this standard due weightage has been given to international co-ordination among the standards and practices prevailing in different countries in addition to relating it to the practices in the field in this country.

0.4 This standard is one of a series of Indian Standards on method of test for natural building stones. Other standards published so far in the series

0.5 In reporting the results of a test or analysis made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS:2-1960*.

1. SCOPE

1.1 This standard lays down the procedure for determining the extent of surface softening taking place in natural building stones when exposed to acidic atmospheres.

*Rules for rounding off numerical values (revised).

2. SAMPLING

2.1 The sample shall be selected to represent a true average of the type or grade of stone under consideration.

2.2 The sample shall be selected by the purchaser or his authorized representative from the quarried stone or taken from the natural rock, as described in 2.2.1 and 2.2.2 and shall be of adequate size to permit the preparation of the requisite number of test pieces.

2.2.1 In case of stone from ledges or quarries the ledge or quarry face of the stone shall be inspected to determine any variation in the different strata. Differences in colour, texture and structure shall be observed. Separate samples of stone weighing at least 25 kg each of unweathered specimen shall be obtained from all strata that appear to vary in colour, texture and structure. Pieces that have been damaged by blasting, driving wedges, heating, etc, shall not be included in the sample.

2.2.2 In case of field stone and boulder, a detailed inspection of the deposits of field stone and boulders over the area where the supply is to be obtained, shall be made. The different kinds of stone and their condition in the various deposits shall be recorded. Separate samples shall be selected for all classes of stone that would be considered for use in construction as indicated by visual inspection.

2.3 When perceptible variations occur in the quality of rock, the purchaser shall select as many samples as are necessary for determining the range in properties.

3. TEST SPECIMENS

3.1 Test pieces shall be either $10 \times 10 \times 20$ cm prisms or 10-cm cubes. The faces shall be ground smooth and finished with abrasive of IS Grit No. 80 (see IS: 715-1966*), and brushed free of all loose flakes.

4. HAND SCRAPING TOOL

4.1 The scraping tool shall be made by grinding down the blade of a putty knife to a length of 7.5 cm and width of 2 cm. The end of the blade shall be ground to a plane surface perpendicular to the length of the tool to form a sharp edge with either side of the blade. These sharp edges shall be referred to as cutting edges, and the scraping shall be done with these cutting edges.

NOTE — The type of steel shall be of T-90 V23 conforming to IS : 1570-1961†.

*Specification for coated abrasives, glue bond (*revised*).

†Schedules for wrought steels for general engineering purposes.

5. TEST PROCEDURE

5.1 Sample Preparation — The specimens tested shall not be less than 3 in number. One of the faces of each sample shall be scraped in the original condition at the centre. The scraping shall be done in the manner as explained in 5.1.1. The centre of the face may be located by drawing the diagonals of the rectangle. The depth of scraping d_1 shall be found by making thickness measurements to the nearest 0.02 mm before and after scraping and computing their difference. The sample shall be scraped at room temperature (20° to 30°C).

5.1.1 Procedure for Scraping — Apply approximately 1.5 kg pressure (see Note below) on the cutting edge holding the blade on the surface of the specimen at an angle of 30° . Make each stroke by moving the cutting edge forward about 4 cm, and repeat the stroke with the same cutting edge 8 times, taking care that each stroke follows the same path. Make another 8 strokes with the other cutting edge in the same manner. Before each specimen is scraped, sharpen the cutting edge.

NOTE — The criteria for judging the pressure to be applied in the test, are the feel of pressure, and the amount of bending of the blade. By grasping the handle of the tool in the same way as in scraping the specimen and by pressing a cutting edge on the weighing table of a small platform scale having its weighing beam set for a load of 1.5 kg, the feel of pressure and the bending of blade could be ascertained.

5.2 After scraping the specimen as in 5.1, put that in a glass vessel and completely cover with 1 percent (w/v) sulphuric acid solution (see Note below). Space the specimens in the container so that the acid has free access to the faces that are to be scraped subsequently as in 5.3. Pour off the acid solution each day and replace with fresh solution. At the end of 7 days remove the specimens, wash thoroughly with water and dry in an oven for 24 hours at $105^\circ \pm 2^\circ\text{C}$.

NOTE — A convenient means of determining the amount of sulphuric acid required to make 1-percent solution is obtained from the following formula:

$$\text{One percent (0.01 } w/v) \text{ sulphuric acid solution} = \frac{0.06 x}{x + 10\,000}$$

where

x = the weight of 96-percent sulphuric acid (sp gr 1.84) to be dissolved in 10 000 ml of water

Therefore, the value of $x = 105.25$ kg

The volume of 105.25 g of such sulphuric acid is $\frac{105.25}{1.84} = 57$ ml.

The error due to assuming the density of water as 1 is not appreciable.

5.3 When the specimens have cooled to room temperature (20° to 30°C) after drying, scrape in each specimen the face opposite to the one scraped

previously as in 5.1. The scraping shall be done in the same manner as explained in 5.1.1. Find the depth of scraping (d_2) by measurement of thicknesses before and after scraping and computing the difference.

6. EVALUATION

6.1 The depth of softening shall be computed for each specimen as ($d_2 - d_1$) (see 5.1 and 5.3). The average depth of softening for all the specimens tested shall be computed and reported. The result shall be expressed to nearest 0.02 mm.

6.2 The following additional information shall be reported:

- a) Identification of the sample, including name and location of the quarry,
- b) Name or position of the ledge,
- c) Date when sample was taken,
- d) Trade name or grade of stone,
- e) Size and shape of the specimen used in the test, and
- f) A description of the manner in which the specimens were prepared.

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 331 01 31, 331 13 75

Telegrams: Manaksanstha
(Common to all Offices)

Regional Offices:

	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002	{ 331 01 31 331 13 75 36 24 99
*Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road. Maniktola, CALCUTTA 700054	{ 2 18 43 3 16 41 41 24 42
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	{ 41 25 19 41 29 16
Southern : C. I. T. Campus, MADRAS 600113	{ 6 32 92 95
†Western : Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMADABAD 380001	{ 2 63 48 2 63 49
‡Peenya Industrial Area 1st Stage, Bangalore Tumkur Road BANGALORE 560058	{ 38 49 55 38 49 56
Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. Nagar, BHOPAL 462003	6 67 16
Plot No. 82/83, Lewis Road, BHUBANESHWAR 751002	5 36 27
53/5, Ward No. 29, R.G. Barua Road, 5th Byelane, GUWAHATI 781003	3 31 77
5-8-56C L. N. Gupta Marg (Nampally Station Road), HYDERABAD 500001	23 10 83
R14 Yudhister Marg, C Scheme, JAIPUR 302005	{ 6 34 71 6 98 32
117/418 B Sarvodaya Nagar, KANPUR 208005	{ 21 68 76 21 82 92
Patliputra Industrial Estate, PATNA 800013	6 23 05
T.C. No. 14/1421, University P.O., Palayam TRIVANDRUM 695035	{ 6 21 04 6 21 17

Inspection Offices (With Sale Point):

Pushpanjali, First Floor, 205-A West High Court Road, Shankar Nagar Square, NAGPUR 440010	2 51 71
Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005	5 24 35

*Sales Office in Calcutta is at 5 Chowringhee Approach, P. O. Princep Street, Calcutta 700072

†Sales Office in Bombay is at Novelty Chambers, Grant Road, 89 65 28
Bombay 400007

‡Sales Office in Bangalore is at Unity Building, Narasimharaja Square, 22 36 71
Bangalore 560002