

X

इंटरनेट

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

"जानने का अधिकार, जीने का अधिकार" Mazdoor Kisan Shakti Sangathan "The Right to Information, The Right to Live"

 $\star \star \star \star \star \star \star \star$

"पुराने को छोड नये के तरफ" Jawaharlal Nehru "Step Out From the Old to the New"

मानक

IS 9459 (1980): Specification for apparatus for use in

measurement of length change of hardened cement paste, mortar and concrete [CED 2: Cement and Concrete]

61119/20

Made Available By Public.Resource.Org

 $\star \star \star \star \star \star \star$

"ज्ञान से एक नये भारत का निर्माण″ Satyanarayan Gangaram Pitroda "Invent a New India Using Knowledge"

RIGHT TO INFORMATION "ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता Bhartrhari-Nītiśatakam "Knowledge is such a treasure which cannot be stolen"



BLANK PAGE



PROTECTED BY COPYRIGHT

IS: 9459 1980 (Reaffirmed 2008)

Indian Standard

SPECIFICATION FOR APPARATUS FOR USE IN MEASUREMENT OF LENGTH CHANGE OF HARDENED CEMENT PASTE, MORTAR AND CONCRETE

(Second Reprint JUNE 1998)

UDC 666.97.015.7 : 620.192.52.05

© Copyright 1980

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

July 1980

Indian Standard

SPECIFICATION FOR APPARATUS FOR USE IN MEASUREMENT OF LENGTH CHANGE OF HARDENED CEMENT PASTE, MORTAR AND CONCRETE

Cement and Concrete Sectional Committee, BDC 2			
Chairman	Representing		
Dr H. C. Visvesvaraya	Cement Research Institute of India, New Delhi		
Members			
ADDITIONAL DIRECTOR, STAND- ARDS (B & S) DEPUTY DIRECTOR, STAND- ARDS (B & S) (Alternate)	Research, Designs & Standards Organization (Ministry of Railways)		
SHRI K. C. AGGARWAL	Hindustan Prefab Ltd, New Delhi		
SHRIC, L, KASLIWAL (Alterna	le)		
SHRI S. K. BANERJEE	National Test House, Calcutta		
SHRIK. P. BANERJEE	Larsen & Toubro Ltd, Bombay		
SHRI MARISH N, MALANI (All	lernale)		
SHRIK, N. DANSAL	Reas Designs Organization, Nangal Lownship		
CHIRF ENGINEER (DESIGNS) EXECUTIVE ENGINEER CHIRF ENGINEER (DESIGNS)	Central Public Works Department, New Delhi		
(DESIGNS) III (Alternate) CHIEF ENGINEER (PROJECTS) DIRECTOR, IPRI (Alternate)	Irrigation Department, Gevernment of Punjab		
DIRECTOR (CSMRS) DEPUTY DIRECTOR (CSMRS) (Alternate)	Central Water Commission, New Delhi		
DR R. K. GHOSH	Central Road Research Institute (CSIR), New Delhi		
SHRI Y. R. PHULL (Alternate I)		
SHRI M, DINAKARAN (Alternal	(e II)		
DR R. K. GHOSH	Indian Roads Congress, New Delhi		
SHBI B. R. GOVIND	Engineer-in-Chief's Branch, Army Headquarters		
SHRIP, C. JAIN (Alternate)			
SHRIA, K. GUPTA	Hyderabad Aspessos Cement Products Ltd, Hyderabad		
DB R. R. HATTIANGADI	The Associated Cement Companies Ltd, Bombay		
SERI P. J. JAGUE (Alternete)	• • • • • •		

(Continued on page 2)

Copyright 1980 BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act, (Continued from page 1)

Members	Representing			
Dr Iqbal Ali	Engineering Research Laboratories, Hyderabad			
SHRIS, R. KULKARNI	M. N. Dastur & Co (Pvt) Ltd, Calcutta			
SHRIS, K. LAHA	The Institution of Engineers (India), Calcutta			
SHRI B. T. UNWALLA (Alternat	•)			
Dr Mohan Rai	Central Building Research Institute (CSIR), Roorkee			
DR S. S. REHBI (Alternate)				
Shri K. K. Nambiar	In personal capacity ('Ramanalaya' 11 First Croscent Park Road, Gandhinagar, Advar, Madras)			
Dr M. Ramaiah	Structural Engineering Research Centre (CSIR), Roorkee			
DB N. S. BHAL (Alternate)				
SHBI G. RAMDAS	Directorate General of Supplies & Disposals, New Delhi			
DR A. V. R. RAO	National Buildings Organization, New Delhi			
SHRI J. SEN GUPTA (Alternate)				
Shri R. V. Chalapathi Rao	Geological Survey of India, Calcutta			
SHBI S. ROY (Alternate)	•			
SHRIT. N. S. RAO	Gammon India Ltd, Bombay			
SHRI S. R. PINHEIRO (Alternati	•)			
SHRI ARJUN RIJHSINGHANI	Cement Corporation of India Ltd, New D 'hi			
SHRI K. VITHAL RAO (Alterna	te)			
SECRETARY	Central Board of Irrigation and Power, N. * Delhi			
DEPUTY SECRETARY (I) (All	ernate)			
SHBI N. SIVAGURU	Roads Wing, Ministry of Shipping and Trai port			
SHRI R. L. KAPOOR (Alternate)			
SHRI K. A. SUBRAMANIAM	The India Cements Ltd, Madras			
SERI P. S. RAMACEANDRAN (Alternate)			
(DESIGNS)	Public Works Department, Government of 'amil Nadu			
EXECUTIVE ENGINEER				
(SM & K DIVISION) (Aller	nale) Delmis Coment (Bharet) Itd. New Delhi			
SHRILL SWAROOP	Daimia Cement (Bharat) Lid, New Deini			
STRIA. V. RAMANA (AMTAMA	The Congress Association of India Bombay			
SUDIV K MUUMA (Aliemaia	The concrete Association of Thum, Domoay			
SPRID ATTELA SIMULA	Director General ISI (Example in Member)			
Director (Civ Engg)	Director Central, 101 (Droghto manuar)			
Secretary				

SHRI M. N. NEELAKANDHAN Assistant Director (Civ Engg), ISI

Instruments for Cement and Concrete Testing Subcommittee, BDC 2:10

Connener	
Gonvener	

DR IQBAL ALI	Engineering Research Laboratories, Hyderabad	
Members		
PROF B. M. AHUJA Shbi T. P. Ekambaram	Indi an Instit ute of Technology, New Delhi Highways Research Station, Madras	

Highways Research Station, Madras

(Continued on page 8)

AMENDMENT NO. 1 NOVEMBER 1984

IS: 9459 - 1980 SPECIFICATION FOR APPARATUS FOR USE IN MEASUREMENT OF LENGTH CHANGE OF HARDENED CEMENT PASTE, MORTAR AND CONCRETE

Alterations

(Page 4, clause 3.1, fifth sentence) — Substitute the following for the existing matter:

'The end of the yoke opposite to the micrometer end of the reference bar shall be provided with an anvil having a cylindrical or conical recess.'

(Page 4, clause 3.1.1, line 5) --- Substitute 'yoke' for 'frame'.

(Page 4, clause 3.2, line 4) - Substitute '12 mm' for '20 mm'.

(Page 5, Fig. 1) - Substitute 'YOKE ' for ' PILLAR '.

(Page 6, Fig. 2) — Substitute the figure given on page 2 for the existing figure.

[Page 7, Table 1, col 3, Sl No. (i)] — Substitute 'ISLC 150 or ISMC 150 conforming to IS : 226-1975[•]' for the existing matter.



VIEW Y

All dimensions in millimetres.

FIG. 2 TYPICAL SET UP FOR DRYING SHRINKAGE AND MOISTURE MOVEMENT TEST ON HEAVY SPECIMEN

.

(BDC 2)

AMENDMENT NO. 2 APRIL 1993 TO

IS 9459 : 1980 SPECIFICATION FOR APPARATUS FOR USE IN MEASUREMENT OF LENGTH CHANGE OF HARDENED CEMENT PASTE, MORTAR AND CONCRETE

(Page 6, clause 3.3) — Substitute the following for the existing clause:

'3.3 Except where the tolerances are specifically indicated against the specified dimensions, all dimensions shall be taken as nominal dimensions with tolerances as laid down in IS 2102 (Part 1): 1980*.'

(Page 6, foot-note) — Insert the following foot-note at the end:

**General tolerances for dimensions and form and position: Part 1 General tolerances for linear and angular dimensions (*second revision*).*

(Page 7, Table 1):

i) Substitute 'Yoke' for 'Pillars' in col 2 of Sl No. (ii).

ii) Delete 'conforming to relevant Indian Standards' from the NOTE.

Indian Standard

SPECIFICATION FOR APPARATUS FOR USE IN MEASUREMENT OF LENGTH CHANGE OF HARDENED CEMENT PASTE, MORTAR AND CONCRETE

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 8 February 1980, after the draft finalized by the Cement and Concrete Sectional Committee had been approved by the Civil Engineering Division Council.

0.2 The Indian Standards Institution has already published a series of standards on methods of testing cement and concrete. It has been recognized that reproducible and repeatable test results can be obtained only with standard testing equipment capable of giving the desired level of accuracy. The Sectional Committee has, therefore, decided to bring out a series of specifications covering the requirements of equipments used for testing cement and concrete, to encourage their development and manufacture in the country.

0.3 Accordingly, this standard has been prepared to cover requirements of the apparatus for use in measurement of length change of hardened cement paste, mortar and concrete. This apparatus may be used for determining the initial drying shrinkage, drying shrinkage and moisture movement of concrete (see IS: 1199-1959*), alkali reactivity of aggregate [see IS: 2386 (Part VII)-1963†] and drying shrinkage of Portland pozzolana cement (see IS: 4031-1968‡).

0.4 In the formulation of this standard, due weightage has been given to international co-ordination among the standards and practices prevailing in different countries in addition to relating it to the practices in the field in this country.

^{*}Methods of sampling and analysis of concrete.

Methods of test for aggregate for concrete: Part VII Alkali aggregate reactivity.

[‡]Methods of physical tests for hydraulic cement,

IS: 9459 - 1980

0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS : 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard lays down the requirements of apparatus (known as length comparator) to measure length change in hardened cement paste, mortar and concrete, using a suitable micrometer.

2. APPARATUS

2.1 The apparatus shall consist of an adjustable length comparator using a screw or dial micrometer, together with a suitable reference bar.

3. CONSTRUCTION AND DIMENSIONS

3.1 The construction of the length comparator shall be as given in Fig. 1 or Fig. 2. The type of apparatus shown in Fig. 2 is recommended for testing heavy specimens, since the pressure caused by the weight of the specimen, which would otherwise fall on the lower reference ball, is carried by the slotted shelf. The apparatus shall preferably be adjustable for specimens of different lengths. Nominal dimensions of the apparatus of the type shown in Fig. 1 are indicated in the figure. The end of the frame to seat the lower end of the reference bar shall be provided with a cylindrical or conical recess. The surfaces in contact with the specimen reference points shall be heat-treated, hardened and polished.

3.1.1 The measuring instrument in the length comparator shall be a high grade micrometer having a range of at least 10 mm and graduated to read in 0.002 mm units, accurate within 0.002 mm in any 0.020 mm range or a suitable dial gauge. This gauge shall be rigidly mounted in a measuring frame and shall have a conical spindle which can be located upon a 6 mm diameter ball or other reference point cemented in the specimen.

3.2 The reference bar against which the readings of the gauge are tested, shall be of stainless steel having a co-efficient of thermal expansion not greater than 2 millionth per deg C. The reference bar may have an overall diameter of 20 mm and of $300 \pm \frac{1}{10}$ mm or $150 \pm \frac{1}{10}$ mm length which

^{*}Rules for rounding off numerical values (revised).

ever is appropriate. The length of the reference bar shall be standardized at a particular temperature and provided with calibration charts for reading length at different temperatures. Each end of the bar shall be machined to 6 mm diameter spherical ends or 6 mm dia balls may be swaged or otherwise fixed to the end. The ends shall be heat-treated, hardened and then polished. The central 100 mm of the length of the bar shall be covered by insulating material, such as 6 mm thick rubber tube, to facilitate handling and to minimize the effect of temperature during handling. The bar shall be provided with a positioning mark near one end.









FIG. 2 TYPICAL SET UP FOR DRYING SHRINKAGE AND MOISTURE MOVEMENT TEST ON HEAVY SPECIMEN

3.3 Except where the tolerances are specifically indicated against the specified dimensions, all dimensions shall be taken as nominal dimensions with tolerances normally applicable in general engineering practice.

4. MATERIAL

4.1 Materials of construction of different component parts of the apparatus shall be as given in Table 1.

TABLE 1 MATERIALS FOR LENGTH COMPARATOR

(Clouse 4.1)

Sl No,	PART	MATERIAL	SPECIAL REQUIREMENTS, IF ANY
i)	Base	Channel mild steel (IS : 226-1975*)	-
ii)	Pillars	Mild steel (IS : 226-1975*)	Threaded for adjustment
iii)	Bracket	Mild steel (IS:226-1975*)	
iv)	Reference bar	Stainless steel	Ends heat-treated, hardened and then polished
v)	Rubber tube	Rubber	

NOTE — All non-working mild steel parts of the apparatus shall be provided suitable anticorrosive treatment such as painting, nitriding and phosphating conforming to relevant Indian Standards.

*Specification for structural steel (standard quality) (fifth revision).

5. MARKING

5.1 The apparatus shall be marked with the following information:

- a) Name of the manufacturer or his trade-mark, and
- b) Date of manfacture.
- 5.1.1 The product may also be marked with Standard Mark.

5.2 The use of the Standard Mark is governed by the provisions of *Bureau of Indian Standards Act*, 1986 and the Rules and Regulations made thereunder. The details of conditions under which the licence for the use of Standard Mark may be granted to manfucaturers or producers may be obtained from the Bureau of Indian Standards.

IS: 9459 - 1980

(Continued from page 2) Members Representing DR R. K. GHOSH Central Road Research Institute (CSIR). New Delhi SHRIK, L. SETRI (Alternate) SHRIH, K. GUHA All India Instruments Manufacturers and Dealers Association, Bombay SHRI V. K. VASUDEVAN (Alternate) The Associated Cement Companies Ltd. Bombay SHRI P. J. JAGUS SHRI D. A. WADIA (Alternate) SHBI M. R. JOSHI Research & Development Organization (Ministry of Defence), Pune SHRIY, P. PATHAK (Alternate) National Test House, Calcutta SHBIE. K. RAMACHANDRAN PROF C. K. RAMESH Indian Institute of Technology, Combay DR R. S. AYYAR (Alternate) SHRI M. V. RANGA RAO Cement Research Institute of India, New Delhi DR K. C. NABANG (Alternate) DR S. S. REHAL Building Research Institute (CSIR), Central Roorkee SHRI J. P. KAUBHISH (Alternate) SHEI M. M. D. SETH Public Works Department, Government of Uttar Pradesh SHRI J. P. BHATNAGAR (Alternate) SHBI H. C. VERMA Associated Instrument Manufacturers (India) Private Ltd, New Delhi SHRI A. V. SHABTRI (Alternate)

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zatar Marg, NEW DELHI 110002 Telephones: 323 0131, 323 3375, 323 9402 Fax: 91 11 3234062, 91 11 3239399, 91 11 3239382

	Telegrams : Manaksanstha (Common to all Offices)
Central Laboratory:	Telephone
Plot No. 20/9, Site IV, Sahibabad Industrial Area, SAHIBABAD 24	01010 8-77 00 32
Regional Offices:	
Central : Manak Bhavan, 9 Bahadur Shah Zatar Marg, NEW DEL	HI 110002 323 76 17
*Eastern : 1/14 CIT Scheme VII M, V.I.P. Road, Maniktola, CALC	UTTA 700054 337 86 62
Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022	60 38 43
Southern C.I.T. Campus, IV Cross Road, CHENNAI 600113	235 23 15
†Western : Manakalaya, E9 Behind Marol Telephone Exchange, A MUMBAI 400093	ndheri (East), 832 92 95
Branch Offices:	
'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 38	10001 550 1 3 48
Peenya Industrial Area, 1st Stage, Bangalore - Turnkur Road, BANGALORE 560058	839 49 55
Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. Nagar, BHO	PAL 462003 55 40 21
Plot No. 62-63, Unit VI, Ganga Nagar, BHUBANESHWAR 75100	1 1 40 36 27
Kalaikathir Buildings, 670 Avinashi Road, COIMBATORE 641037	<u>ે</u> 21 01 41
Piot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001	8-28 88 01
Savitri Complex, 116 G. T. Road, GHAZIABAD 201001	8-71 19 96
53/5 Ward No. 29, R. G. Barua Road, 5th By-lane, GUWAHATI 7	/81003 / 54 11 37
5-8-58C, L. N. Gupta Marg, Nampally Station Road, HYDERABA	D 500001 👔 🖕 20 10 83
E-52, Chitaranjan Marg, C-Scheme, JAIPUR 302001	37 29 25
117/418 B, Sarvodaya Nagar, KANPUR 208005	21 68 76
Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Ro LUCKNOW 226001	oad, 23 89 23
Patliputra Industrial Estate, PATNA 800013	26 23-05
T. C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPURAM 695034	6 21 17
NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010	52 51 71
Institution of Engineers (India) Building, 1332 Shivaji Nagar, PU	NE 411005 32 36 35
"Sales Office is at 5 Chowringhee Approach, P. O. Princep Stree	t,
GALGUTTA 700072	-27 10 85
TSales Unice is at Novelty Chambers, Grant Hoad, MUMBAI 40	309 65 28
TSales Office is at 'F' Block, Unity Building, Narashimaraja Squa BANGALORE 560002	re, 222 39 71