

BLANK PAGE



IS 2673: 2002

भारतीय मानक

पिटवाँ ऐल्युमीनियम एवं ऐल्युमीनियम मिश्र धातुओं से बनी एक्सटूडेड गोल नलियों के आयाम — विशिष्टि (दूसरा पुनरीक्षण)

Indian Standard

DIMENSIONS FOR WROUGHT ALUMINIUM AND ALUMINIUM ALLOYS EXTRUDED ROUND TUBE — SPECIFICATION

(Second Revision)

ICS 77.150.10

© BIS 2002

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

FOREWORD

This Indian Standard (Second Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Light Metals and Their Alloys Sectional Committee had been approved by the Metallurgical Engineering Division Council.

This standard was first published in 1964 and subsequently revised in 1979. While reviewing this standard in the light of experience gained during these years, the Sectional Committee decided to revise the standard.

In this revision, dimensions and tolerances for extruded seamless tubes have been included. Similarly, for ease of references, clause on terminology has been added.

The composition of the Committee responsible for formulation of this standard is given in Annex A.

For the purpose of deciding whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2:1960 'Rules for rounding off numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

DIMENSIONS FOR WROUGHT ALUMINIUM AND ALUMINIUM ALLOYS EXTRUDED ROUND TUBE — SPECIFICATION

(Second Revision)

1 SCOPE

This standard specifies the dimensions and tolerances for extruded round tubes made from wrought aluminium and aluminium alloys.

2 REFERENCES

The following Indian Standards contain provisions which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below:

IS No.	Title
1285 : 2002	Wroght aluminium and aluminium alloys — Extruded round tube and
	hollow sections for general engine-
	ering purposes — Specification (third revision)
5047	Glossary of terms relating to aluminium and aluminium alloys:
(Part 1): 1986	Unwrought and wrought metals (second revision)
(Part 2): 1979	Plant and operations, thermal treat-
(Part 3): 1979	ment, control and testing, finishing Geometrical properties and tolerance,
	structural and surface defects

3 TERMINOLOGY

For the purpose of this standard the definitions are given in IS 1285 and IS 5047 (Parts 1, 2 and 3) shall apply.

4 STANDARD SIZES

- **4.1** The standard outside diameters and thickness of structural tubes shall be as given in Table 1.
- **4.2** The standard outside diameters and thickness of seamless tubes shall be as given in Table 2.

5 TOLERANCE ON STANDARD SIZES

- 5.1 Tolerance on wall thickness of structural tubes shall be as given in Table 3.
- **5.2** Tolerance on wall thickness of seamless tubes shall be as given in Table 4.
- **5.3** Tolerance on outside or inside diameter of structural tubes shall be as given in Table 5.
- **5.4** Tolerance on outside or inside diameter of seamless tubes shall be as given in Table 6.

5.5 Straightness Tolerance

All tubes shall be supplied in straight condition. The straightness tolerance (see Fig. 1) for tubes shall be as follows:

Туре	Allowable Deviation
	from Straightness
	(mm/m of length)
Structural Tubes	1.7
Seamless Tubes	2.1

5.6 Length Tolerance

Unless otherwise agreed, the length tolerances shall be as given in Table 7.




FIG. 1 STRAIGHTNESS TOLERANCE FOR EXTRUDED ROUND TUBES

Table 1 Standard Sizes of Extruded Structural Tubes

(Clause 4.1)
All dimensions in millimetres.

Wall Thickness	Outside Diameter
1.20 1.60 1.80 2.00	9.0, 12.0, 14.0, 16.0, 18.0, 20.0, 22.0, 25.0, 28.0, 32.0, 36.0, 40.0, 45.0, 50.0
2.24 2.50	12.0, 14.0, 16.0, 18.0, 20.0, 22.0, 25.0, 28.0, 32.0, 36.0, 40.0, 45.0, 50.0, 56.0, 63.0, 71.0, 80.0
2.80 3.15	12.0, 14.0, 16.0, 18.0, 20.0, 22.0, 25.0, 28.0, 32.0, 36.0, 40.0, 45.0, 50.0, 56.0, 63.0, 71.0, 80.0, 90.0, 100.0
3.55 4.00	12.0, 14.0, 16.0, 18.0, 20.0, 22.0, 25.0, 28.0, 32.0, 36.0, 40.0, 45.0, 50.0, 56.0, 63.0, 71.0, 80.0, 90.0, 100.0, 110.0, 125.0, 140.0
4.50 5.00	28.0, 32.0, 36.0, 40.0, 45.0, 50.0, 56.0, 63.0, 71.0, 80.0, 90.0, 100.0, 110.0, 125.0, 140.0, 160.0, 180.0, 200.0
5.60 6.30	36.0, 40.0, 45.0, 50.0, 56.0, 63.0, 71.0, 80.0, 90.0, 100.0, 110.0, 125.0, 140.0, 160.0, 180.0, 200.0, 220.0, 250.0
7.10 8.00	45.0, 50.0, 56.0, 63.0, 71.0, 80.0, 90.0, 100.0, 110.0, 125.0, 140.0, 160.0, 180.0, 200.0, 220.0, 250.0
9.00 10.00 11.20 12.50	56.0, 63.0, 71.0, 80.0, 90.0, 100.0, 110.0, 125.0, 140.0, 160.0, 180.0, 200.0, 220.0, 250.0
14.0 16.00	71.0, 80.0, 90.0, 100.0, 110.0, 125.0, 140.0, 160.0, 180.0, 200.0, 220.0, 250.0
18.00 20.00 22.40 25.00	90.0, 100.0, 110.0, 125.0, 140.0, 160.0, 180.0, 200.0, 220.0, 250.0

be as agreed to between the supplier and the purchaser.

Table 2 Standard Sizes of Extruded Seamless Tubes

(Clause 4.2)
All dimensions in millimetres.

42, 45, 48, 50, 56, 60, 63, 66, 72, 80, 88, 102 48, 50, 56, 60, 63, 66, 72, 80, 88, 102, 115
48, 50, 56, 60, 63, 66, 72, 80, 88, 102, 115
48, 50, 56, 60, 63, 66, 72, 80, 88, 102, 115
48, 50, 56, 60, 63, 66, 72, 80, 88, 102, 115
60, 63, 66, 72, 80, 88, 102, 115, 125
75, 80, 88, 102, 115, 125
88, 102, 115, 125, 140
· ·
· · · · · · · · · · · · · · · · · · ·
102, 115, 125, 140

Table 3 Tolerances on Wall Thickness of Extruded Structural Tube

(Clause 5.1)
All dimensions in millimetres

Specified Wall Thickness	Outside Diameter	
	Class 1	Class 2
	±	±
Up to 1.2	0.30	~
1.60	0.30	-
1.80	0.30	_
2.00	0.30	
2.24	0.30	_
2.50	0.33	_
2.80	0.36	
3.15	0.40	0.90
3.55	0.43	0.94
4.00	0.48	0.97
4.50	0.51	1.02
5.00	0.56	1.07
5.50	0.61	1.12
6.30	0.67	1.18
7.10	0.76	1.27
8.00	0.97	1.47
9.00	1.10	1.60
10.00	1.22	1.73
11.20	1.28	1.79
12.50	1.35	1.85

NOTES

- 1 Tubes with wall thickness intermediate between standard sizes will have the tolerance of the next higher wall thickness.
- 2 Tolerances on standard wall thickness above 12.50 mm may be as agreed to between the purchaser and the supplier.
- 3 For Al-Zn-Mg, Al-Mg and Al-Cu alloys, Class 2 tolerances shall apply.
- 4 For Al, Al-Mn and Al-Mg-Si alloys, Class 1 tolerances shall apply.

Table 4 Tolerances on Wall Thickness of Extruded Seamless Tube

(Clause 5.2)
All dimensions in millimetres

Specified Wall	Tolerance
Thickness	±
3.50	0.63
4.00	0.70
4.50	0.76
5.00	0.82
5.50	0.88
6.00	0.93
6.50	0.97
7.00	1.01
8.00	1.14
9.00	1.21
10.00	1.30
11.50	1.44
13.00	1.56
14.50	1.67
16.00	1.76

- 1 Tubes with wall thickness intermediate between standard size: will have the tolerance of the next higher wall thickness.
- 2 Tolerances on wall thickness above 16.00 mm shall be as agreed to between the purchaser and the supplier.
- 3 For A1-Zn-Mg, A1-Mg and A1-Cu alloys, tolerance shall be one and half times of that specified in the table.

Table 5 Tolerance on Diameter (Inside and Outside) of Extruded Structural Tubes

(Clause 5.3)

All dimensions in millimetres.

Specified Diameter (Outside or Inside)		Allowable Deviation of Mean Diameter from Specified Diameter (Size Tolerance)	Allowable Deviation of Diameter at Any Point from Specified Diameter (Ovality Tolerance)
			A
		Difference Between $\frac{1}{2}(AA + BB)$ and Specified Diameter	Difference Between AA and Specified Diameter
		±	±
From 9 up to and including	18	0.25	0.50
Above 18 up to and including	30	0.30	0.60
Above 30 up to and including	40	0.36	0.80
Above 40 up to and including		0.45	0.90
Above 50 up to and including	60	0.54	1.00
Above 60 up to and including	80	0.60	1.30
Above 80 up to and including		1 % of dia	2.5% of dia

NOTES

- 1 When outside diameter, inside diameter and wall thickness are all specified, standard tolerances are applicable to any two of these dimensions, but not to all three.
- 2 Mean diameter is the average of two diameter measurements taken at right angles to each other at any point along the length. In other words, mean diameter is 1/2 (AA + BB).
- 3 Ovalness tolerance is not applicable for annealed temper or if the wall thickness is less than 2.5 percent of the outside diameter.
- 4 For alloys having magnesium as main alloying element, the tolerance shall be one and half times that specified in the table.

Table 6 Tolerance on Diameter (Inside and Outside) of Extruded Seamless Tubes

(Clause 5.4)

All dimensions in millimetres.

Specified Diameter (Outside or Inside)		Allowable Deviation of Mean Diameter from Specified Diameter (Size Tolerance) ±	Allowable Deviation of Diameter at Any Point from Specified Diameter (Ovality Tolerance) ±
			A
From 20 up to and including	30	0.42	0.70
Above 30 up to and including	40	0.48	0.80
Above 40 up to and including	50	0.60	1.00
Above 50 up to and including	60	0.72	1.20
Above 60 up to and including	80	0.96	1.60
Above 80 up to and including	100	1.20	2.00
Above 100 up to and including	_	1.50 % of dia	2.5% of dia

NOTES

- 1 When outside diameter, inside diameter and wall thickness are all specified, standard tolerances are applicable to any two of these dimensions, but not to all three.
- 2 Mean diameter is the average of two diameter measurement taken at right angles to each other at any point along the length.
- 3 Ovalness tolerance is not applicable for annealed temper or if the wall thickness is less than 2.5 percent of the outside diameter.
- 4 For alloys having copper, magnesium or zinc as main alloying element, the tolerance shall be one and half times that specified in the table.

Table 7 Tolerances on Lengths

(Clause 5.6)

All dimensions in millimetres.

Nomi	nal Diameter	Length			
Over	Up to and Including	Up to and Including 1 500	Over 1 500 Up to and Including 6 000	Over 6 000	
-	50	±4	±5	±6	
50	100	±5	±6	±7	
100	150	±6	±7	±8	
150	-	±7	±8	±9	

ANNEX A

(Foreword)

COMMITTEE COMPOSITION

Light Metals and Their Alloys Sectional Committee, MTD 7

_		
Organ	inn	tian
vizui	u.	LLUIL

In personal capacity, (Flat No. 102 Rohtas Court, 15 Gokhale Marg, Lucknow-226001)

Aeronautical Development Establishment, Bangalore

Aluminium Association of India, Bangalore

Bharat Aluminium Co Ltd. Korba/New Delhi

Bharat Forge Ltd. Pune

Bharat Heavy Electricals Ltd, Bhopal/Hyderabad

CEMILAC, Ministry of Defence, Bangalore Central Electricity Authority, New Delhi

Central Electrochemical Research Institute, Karaikudi

Central Power Research Institute, Bangalore

Civil Aviation Department, Bangalore/New Delhi

Directorate General Suppliers and Disposal (Inspection Wing), New Delhi/Bhilai

Defence Research & Development Laboratory, Hyderabad

Development Commissioner (SSI), New Delhi Electrical Manufacturing Co Ltd, Kolkata Galada Continuous Castings Ltd, Hyderabad Heat Treaters and Engineers, Mumbai Hindalco Industsries Ltd, Renukoot

Hindustan Aeronautics Ltd, Bangalore

ISRO (VSSC), Thiruvananthapuram India Foils Ltd, Kolkata

India Pistons Ltd, Chennai

Indian Aluminium Co Ltd, Taloja/Kolkata

Indira Gandhi Centre for Atomic Research, Kalpakkam

Institute of Indian Foundrymen, New Delhi

J.L.N. Aluminium R&D and Design Centre, Nagpur

Representative(s)

SHRI V. K. AGRAWAL (Chairman)

SHRIN.C. SUD

SHRIMATI CHHAYA RAJPUT (Alternate)

PROF K. S. S MURTHY

SHRI K. S. NAGESH (Alternate)

SHRI D. K. BISWAS

SHRI S. M. CHOBEY (Alternate I)
SHRI V. K. VASUDEVA (Alternate II)

SHRI N. R. HABBU

SHRI A. R. CHAUTHAI (Alternate)

SHRI R. K. SETH

SHRI C. KANNAN (Alternate)

Dr.P. RAGHOTHAMA RAO

SHRI KARNAIL SINGH

SHRI NARENDER SINGH (Alternate)

SHRI A. SELVAKESAVAN

Dr V. Ananth (Alternate)

Dr Seetharamu

SHRI B. H. NARAYANA (Alternate)

SHRI R. C. GUPTA

SHRI M. M. WALECHA (Alternate)

Shri B. B. Rai

SHRI S. K. PANDEY (Alternate)

Dr S. Sundarajan

SHRI G. RAJA SINGH (Alternate)

DIRECTOR (MET)

SHRI G. K. GHOSH

SHRI D. C. GALADA

SHRI SANDEEP PARIKH

SHRI J. P. SINGH

SHRI ABHAY AGARWAL (Alternate)

DR P. K. SENGUPTA

SHRI D. DUTTA (Alternate)

DR P. K. BALASUBRAMANIAM

REDDESENTATIVE

SHRI N. GOWRISHANKAR

SHRI S. SUNDARAJAN (Alternate)

SHRI S. V. DESAI

SHRI S. GUPTA (Alternate)

SHRIK, V. KASIVISWANATHAN

SHRI UDAYAN SEN

Dr V. V. KUTUMBARAO

IS 2673: 2002

(Continued from page 5)

Organization

Jindal Aluminium Ltd, Bangalore

Ministry of Defence (DGAQA), Hyderabad

Ministry of Defence (DGQA), Ichapur

Ministry of Defence (DMRL), Hyderabad

Ministry of Defence (OFB), Ambernath

National Aerospace Laboratory, Bangalore National Aluminium Co Ltd, Bhubaneswar

National Metallurgical Laboratory, Jamshedpur National Thermal Power Corporation, Noida

Research Designs and Standards, Lucknow

Rural Electrification Corporation, New Delhi BIS Directorate General Representative(s)

SHRIK. R. RACHUNATH

SHRI S. C. AGRAWAL (Alternate)

Shri K. N. Sinha

SHRI V. K. SACHDEVA (Alternate)

SHRI A. BHATTACHARYA

SHRI P. K. L. R. NIMONKAR (Alternate)

DR AMOL A. GOKHALE

SHRI VIJAY SINGH (Alternate)

Dr S. K. PANDEY

SHRI P. R. JADAV (Alternate)

Dr R. V. Krishnan

SHRI M. M. SETH

SHRI S. P. MOHAPATARA (Alternate)

SHRI KISHORI LAL

REPRESENTATIVE

DIRECTOR (M&C-I)

DIRECTOR (CARRIAGE)/I&L (Alternate I)

ARO (MET-V) (Alternate II)

REPRESENTATIVE

SHRI JAGMOHAN SINGH, Director & Head (MTD) [Representing Director General (Ex-officio)]

Member Secretary
Shri Deepak Jain
Joint Director (MTD), BIS

Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amend No.

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc: No. MTD 7 (4283).

Amendments Issued Since Publication

Date of Issue

Amei	10 NO.	Date of issue	Text Affected
	BU	REAU OF INDIAN STANDARDS	
Headquarte	rs:		
	ivan, 9 Bahadur Shah Zafar I : 323 01 31, 323 33 75, 323		Telegrams: Manaksanstha (Common to all offices)
Regional O	ffices:		Telephone
Central :	Manak Bhavan, 9 Bahadu NEW DELHI 110 002	Shah Zafar Marg	$\begin{cases} 323 & 76 & 17 \\ 323 & 38 & 41 \end{cases}$
Eastern :	1/14 C.I.T. Scheme VII M, KOLKATA 700 054	V. I. P. Road, Kankurgachi	\begin{cases} 337 84 99, 337 85 61 \\ 337 86 26, 337 91 20 \end{cases}
Northern:	SCO 335-336, Sector 34-A	, CHANDIGARH 160 022	$ \begin{cases} 60 38 43 \\ 60 20 25 \end{cases} $
Southern:	C.I.T. Campus, IV Cross R	coad, CHENNAI 600 113	{254 12 16, 254 14 42 254 25 19, 254 13 15
Western :	Manakalaya, E9 MIDC, M MUMBAI 400 093	Iarol, Andheri (East)	832 92 95, 832 78 58 832 78 91, 832 78 92
Branches:	AHMEDABAD. BANGAL	ORE. BHOPAL. BHUBANESHWA	R. COIMBATORE. FARIDABAD.

GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. NAGPUR. NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM. VISAKHAPATNAM

Text Affected