

⇒ PREAMBLE—NOT PART OF THE SPECIFICATION ⇐

In order to promote public education and public safety, equal justice for all, a better informed citizenry, the rule of law, world trade and world peace, this legal document is hereby made available on a noncommercial basis, as it is the right of all humans to know and speak the laws that govern them.

The reader is advised:

- In this file, Public.Resource.Org has transformed this specification into the Hypertext Markup Language (HTML) for the purpose of making these provisions more accessible and more usable.
- This specification is being considered for incorporation by reference into federal law by the Consumer Product Safety Commission as part of the Safety Standard for Garage Door Openers ([80 FR 53036](#)).
- Public.Resource.Org has made no changes to this specification. Any errors in the transformation of this specification should be reported to [Public.Resource.Org](#).
- This file is based on the HTML 5, MathML, SVG, and CSS specifications and may not be compatible with some older browsers.
- Users may wish to modify this file. In particular, the header section calls the [MathJax](#) library and users may wish to use native MathML instead. There are also two calls to Google Fonts and one to our own external style sheet.
- This document is identical to [ANSI/DASMA 102-2011](#) with three exceptions. Instead of incorporating [Chart 1](#), the 2011 version refers to [DASMA Technical Data Sheet 154](#), the reference to the ASME standard in [Section 3](#) of the 2004 version has been dropped in 2011, and there is a slightly different paragraph 3 in the [Foreword](#) referring to the process of ANSI approval.
- This document is available in [HTML](#) and [PDF](#) formats.
- Public.Resource.org is not affiliated in any way with any of the organizations named herein.

⇒ END OF PREAMBLE—NOT PART OF THE SPECIFICATION ⇐

ANSI/DASMA 102-2004

AMERICAN NATIONAL STANDARD

SPECIFICATIONS FOR SECTIONAL DOORS

Door & Access Systems Manufacturers' Association, International

1300 Sumner Ave
Cleveland, Ohio 44115-2851

American National Standard implies a consensus of those substantially concerned with its scope and provisions. A American National Standard is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of a American National Standard does not in any respect preclude anyone, whether he has approved the standard or not, from manufacturing, marketing, purchasing or using products, processes, or procedures not conforming to the standard. American National Standards are subject to periodic review and users are cautioned to obtain the latest editions.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of publication. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Sponsored and published by:

DOOR & ACCESS SYSTEMS MANUFACTURERS' ASSOCIATION, INTERNATIONAL
1300 Sumner Avenue
Cleveland, OH 44115-2851
Phn: 216/241-7333
Fax: 216/241-0105
E-Mail: dasma@dasma.com
URL: www.dasma.com

Copyright © 2004 by Door & Access Systems Manufacturers' Association, International
All Rights Reserved

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Suggestions for improvement of this standard will be welcome. They should be sent to the Door & Access Systems Manufacturers' Association, International.

Printed in the United States of America

American National Standard

TABLE OF CONTENTS

Foreword

1. Scope
2. Definitions
3. Referenced Standards
4. Installation/Operation
5. Maintenance
6. Durability
7. Identification
8. General Requirements
9. Loads
10. Responsibilities Of Others
11. Disclaimers

Foreword

This foreword is included for information only and is not part of ANSI/DASMA 102, *Specifications for Sectional Doors*.

This standard was originally developed by the Technical Committee of the National Association of Garage Door Manufacturers and was approved as an American National Standard with the designation ANSI/NAGDM 102. The Door & Access Systems Manufacturers' Association, International, (DASMA) was formed through the consolidation of two associations that served the garage door and operator industries

for many years, NAGDM and the Door Operator & Remote Control Manufacturers Association (DORCMA).

The Technical Committee of the DASMA Commercial & Residential Garage Door Division has reviewed the standard and has incorporated many revisions and updates, effective May 30, 2003. DASMA employs the canvass method to demonstrate consensus and to gain approval as an American National Standard. When printed, this standard was entering the canvass approval process. The ANSI Board of Standards Review granted approval of the edition as an American National Standard on October 22, 2004.

DASMA recognizes the need to periodically review and update this standard. Suggestions for improvement should be forwarded to the Door & Access Systems Manufacturers' Association, International, 1300 Sumner Avenue, Cleveland, Ohio, 44115-2851.

ANSI/DASMA 102-2004
AMERICAN NATIONAL STANDARD
Specifications for Sectional Doors

1. SCOPE

1.1. Inclusions. This specification for sectional doors, as defined in [Section 2](#), is intended to cover residential and commercial type doors normally used on garages, warehouses, factories, service stations, and other places requiring doors generally used for vehicular traffic.

1.2. Exclusions. It is not intended to cover doors generally used for pedestrian traffic nor other types of overhead doors such as rigid, folding, multi-leaf, rolling curtain doors, or special application doors.

2. DEFINITIONS

2.1 Commercial Door. A sectional door which is intended for vehicular use at entrances of commercial buildings such as loading docks, service stations, parking garages and manufacturing plants, normally expected to be operated but not limited to less than 5,000 cycles per year.

2.2 Cycle. One cycle of a door is complete when it is moved from the closed position to the fully open position and returned to the closed position.

2.3 Door System. Sections and components necessary to produce an operational door per DASMA 102. This may include an operator, if listed as part of the door system.

2.4 Door System Manufacturer. Supplies as a package all sections and components necessary to produce an operational door per DASMA 102. This may include an operator, if listed as part of the door system.

2.5 Folding Door. A door made of two or more horizontal sections that are hinged together but fold one against the other when opened.

2.6 Multi-Leaf Door. A door made of two or more stacking horizontal sections which interlock without the benefit of hinges.

2.7 Power Assisted. Providing a powered device to operate a door system.

2.8 Residential Door. A sectional door which is intended for use in a residential garage, and normally expected to be operated less than 1,500 cycles per year.

2.9 Rigid Doors. A door made in one rigid piece designed to close an entire opening. Opening and closing is accomplished by pivoting the door about an axis, with or without a horizontal track to guide the top of the door.

2.10 Rolling Curtain Door. A door made of individual horizontal interlocking slats. The door is opened by rolling the door around a shaft and subsequently upon itself.

2.11 Sectional Type Doors. Doors made of two or more horizontal sections hinged together so as to provide a door large enough to close the entire opening and which is guided into the horizontal tracks, or into the vertical position by means of an extended vertical track system.

(NOTE: A glossary of common industry terms can be found in [DASMA Technical Data Sheet #160](#)).

3. REFERENCED STANDARDS

The following standards are a part of this standard to the extent that they are referenced in the text. Conformance shall be to the latest edition of each referenced standard listed below.

- [ANSI/DASMA 103](#) *Standard for Counterbalance Systems on Residential Sectional Garage Doors*
- [ANSI/DASMA 105](#) *Test method for thermal transmittance and air infiltration of garage doors*
- [ANSI/DASMA 107](#) *Room Fire Test Standard for Garage Doors Using Foam Plastic Insulation*
- [ANSI/DASMA 108](#) *Standard Method for Testing Sectional Garage Doors: Determination of Structural Performance Under Uniform Static Air Pressure Difference*
- [ANSI/DASMA 109](#) *Standard Method for Testing Garage Doors: Determination of Cycle Life*
- [ANSI/DASMA 115](#) *Standard Method for Testing Garage Doors: Determination of Structural Performance Under Missile Impact and Cyclic Wind Pressure*
- [ANSI/DASMA 116](#) *Standard for Section Interfaces on Residential Garage Door Systems*
- UL 325 *Door, drapery, gate, louver, window operators and systems*
- ANSI/ASME B18.6.2 *Slotted head cap screws, square head set screws, and slotted headless set screws*

4. INSTALLATION/OPERATION

The door system manufacturer shall furnish standard details and instructions for proper installation and operation. Such instructions shall include warnings relative to the installation and operation of the door system.

5. MAINTENANCE

The door system manufacturer shall furnish a listing of those components requiring regular maintenance with instructions and frequencies for such maintenance.

6. DURABILITY

6.1 Residential and commercial door systems shall be designed to operate at a minimum of 10,000 cycles when they are properly selected, installed, operated, and maintained. A door system shall be designed to operate the specified cycle life when more than 10,000 cycles are specified.

6.2 When testing is performed to determine cycle life, testing shall be conducted in accordance with [ANSI/DASMA 109](#).

7. IDENTIFICATION

Each door system shall be labeled to identify the name and address of the door system manufacturer.

8. GENERAL REQUIREMENTS

8.1 Hand Chain Hoist Operation

Hand chain hoists shall not be used on standard lift and low headroom applications unless provisions are made to maintain adequate cable tension as specified by the door system manufacturer.

8.2 Power Assisted Operation

8.2.1 Motorized jackshaft operators shall not be used on standard lift and low headroom applications unless provisions are made to maintain adequate cable tension as specified by the door system manufacturer.

8.2.2 If a drawbar operator is used, additional door reinforcement may be required upon installation. Reinforcement requirements for drawbar attachment shall be specified in the door system manufacturer's installation instructions.

8.2.3 If an operator is listed as part of the door system, such operator shall be designed in compliance with the applicable sections of the version of UL 325 in effect at the time of manufacture.

8.3 Counterbalance Assemblies

8.3.1 Counterbalance assemblies shall meet the requirements of [ANSI/DASMA 103](#).

8.3.2 Torsion spring counterbalance assembly design shall be in accordance with [Section 9.3](#).

8.3.3 Extension spring assembly design shall be in accordance with [ANSI/DASMA 103](#).

8.4 Sectional Door Interfaces and Lift Handles. Residential doors shall meet the requirements of [ANSI/DASMA 116](#).

8.5 Thermal Transmittance/Air Infiltration. Published thermal transmittance and air infiltration values of installed residential and commercial doors shall be in accordance with the test methods specified in [ANSI/DASMA 105](#).

8.6 Published steel gauge numbers shall be in accordance with [Chart 1](#).

8.7 Foam Plastic Insulation. Foam plastics used in sectional doors shall meet requirements established by the authority having jurisdiction for flame spread and smoke development.

9. LOADS

9.1 Wind Loads

9.1.1 Residential or Commercial Door System. A door system shall be designed to withstand a minimum wind load as required by the authority having jurisdiction over the geographic location where the door is to be installed. When required by the authority having jurisdiction, structural tests shall be in accordance with [ANSI/DASMA 108](#) or other accepted means required by the authority having jurisdiction.

9.1.2 Where resistance to windborne debris is required by the authority having jurisdiction over the geographic location where the door is to be installed, a door system shall meet the requirements of **ANSI/DASMA 115** or other accepted means as required by the authority having jurisdiction.

CHART 1: DASMA STEEL GAUGE CHART

GAUGE NO.	BARE	G-10	G-30	G-40	G-60	G-90
10	0.1285	0.1287	0.1290	0.1292	0.1295	0.1300
11	0.1136	0.1138	0.1141	0.1143	0.1146	0.1151
12	0.0986	0.0988	0.0991	0.0993	0.0996	0.1001
13	0.0847	0.0849	0.0852	0.0854	0.0857	0.0862
14	0.0697	0.0699	0.0702	0.0704	0.0707	0.0712
15	0.0623	0.0625	0.0628	0.0630	0.0633	0.0638
16	0.0548	0.0550	0.0553	0.0555	0.0558	0.0563
17	0.0498	0.0500	0.0503	0.0505	0.0508	0.0513
18	0.0438	0.0440	0.0443	0.0445	0.0448	0.0453
19	0.0388	0.0390	0.0393	0.0395	0.0398	0.0403
20	0.0329	0.0331	0.0334	0.0336	0.0339	0.0344
21	0.0299	0.0301	0.0304	0.0306	0.0309	0.0314
22	0.0269	0.0271	0.0274	0.0276	0.0279	0.0284
23	0.0239	0.0241	0.0244	0.0246	0.0249	0.0254
24	0.0209	0.0211	0.0214	0.0216	0.0219	0.0224
25	0.0179	0.0181	0.0184	0.0186	0.0189	0.0194
26	0.0159	0.0161	0.0164	0.0166	0.0169	0.0174
27	0.0144	0.0146	0.0149	0.0151	0.0154	0.0159
28	0.0129	0.0131	0.0134	0.0136	0.0139	0.0144
29	0.0115	0.0117	0.0120	0.0122	0.0125	0.0130
30	0.0100	0.0102	0.0105	0.0107	0.0110	0.0115
NOTES: CHART REPRESENTS UNPAINTED THICKNESS MINIMUMS (IN INCHES) PER GAUGE NUMBER AND SEVERAL COMMON GALVANIZING WEIGHTS. CHART IS BASED ON AISI REFERENCES AND TOLERANCES. BARE STEEL THICKNESSES REPRESENT STEEL WITHOUT THE ADDITION OF GALVANIZING.						

9.2 Dead Loads

9.2.1 Residential and Commercial Door Sections. Door sections, including their reinforcement hinges, roller assemblies, and method of attachment to the door, shall be designed to support their own weight when in the horizontal position and not deflect more than 1/120th of the door width. Deflection shall be measured after the door has been in the horizontal position for at least 24 hours.

9.2.2 Horizontal Track Assembly. The horizontal track assembly, including installation hardware, shall be designed to support a dead load equal to the door weight when in the horizontal position and not deflect more than 1/240th of the door height. Deflection shall be measured after the door has been in the horizontal position for at least 24 hours. Twist, deflection, or deformation of the track shall not interfere with the operation of the door. The manufacturer shall specify the point(s) where attachment to the horizontal track shall be made for the purpose of suspending the track from the building.

9.2.3 Bottom Corner Bracket. Each bottom corner assembly, and its method of attachment to the door, shall be designed to support a dead load equal to the weight of the door, and all on-the-door hardware, multiplied by a safety factor of 2.

9.3 Torsion Spring Counterbalance Assembly. The torsion spring counterbalance assembly shall be so designed and constructed to provide for a safe and durable conversion of spring torque to lifting power for balancing the weight of a sectional door as stated in paragraphs [9.3.1-9.3.6](#). Torsion springs shall not be used to balance sectional doors employing an index ratio of less than 6 to 1 (mean coil diameter six times wire diameter).

$$IR = \frac{MCD}{d}$$

IR = Index Ratio

MCD = Mean Coil Diameter

d = Wire Diameter

9.3.1 Torsion Shafts

9.3.1.1 Tubular steel torsion shafts shall be of a sufficient wall thickness to prevent a torsional (radial) deflection of the shaft in excess of 1.5 degrees per foot (305 mm) of shaft length from the torque source to point of delivery. Linear deflection of a torque shaft shall not exceed one tenth inch (2.5 mm) per foot (305 mm) of shaft length with proper supports in position.

9.3.1.2 Solid steel torsion shafts shall be of a diameter and composition sufficient to prevent torsional (radial) deflection of not more than 2 degrees per foot (305 mm) of shaft length from the torque source to the point of delivery. Linear deflection of the torque shaft shall not exceed one tenth inch (2.5 mm) per foot (305 mm) of shaft length with proper shaft supports in position.

FORMULAS

Formulas are used to determine the angular torsional deflection in degrees for tubular wall and solid torque shafts of any wall thickness or shaft diameter. No allowance made for torsional shear modular loss by set screw deformation of tubular shafts, or keyways milled into solid shafts.

Tubular steel shaft formula:

$$a = \frac{584 \times \text{MIP} \times 12}{(D^4 - d^4) \times 11,500,000}$$

Solid steel shaft formula:

$$a = \frac{584 \times \text{MIP} \times 12}{D^4 \times 11,500,000}$$

Formulas used to determine maximum inch/pound torque limits for a specified number of degrees of torsional deflection per foot of shaft length.

Tubular steel shaft formula:

$$\text{MIP} = \frac{a \times (D^4 - d^4) \times 11,500,000}{584 \times 12}$$

Solid steel shaft formula:

$$\text{MIP} = \frac{a \times D^4 \times 11,500,000}{584 \times 12}$$

Explanation of factors involved in formulas:

a = Angle in degrees deflection per foot of shaft length

MIP = Maximum inch/pounds torque

D^4 = Outside shaft diameter to the 4th power

d^4 = Inside shaft diameter to the 4th power

9.3.2 Cable drums shall be so designed to allow cable to be accumulated or dispensed in an orderly manner and to prevent lapping or cable chafing. Cable drums shall be selected with a minimum safety factor of 4, based on the maximum torque for the applied load requirements.

9.3.3 Spring Fittings

9.3.3.1 Winding device shall have a torsional safety factor of 4. The portion of the winding device interconnecting with the spring shall be of a design that properly retains a torsion spring when fully wound or unwound, and withstands the radial and lateral forces exerted by the torsion springs.

9.3.3.2 Spring retainers and stationary sleeves shall have a torsional safety factor of 4. Spring retainers, or stationary sleeves, shall be so designed to withstand the radial and lateral forces exerted by the torsion spring to properly retain the spring when fully wound or unwound and allow the application of torque.

9.3.4 Each side bearing plate shall be designed to support the weight of the counterbalance assembly, plus the total door weight, multiplied by a safety factor of 2. They shall be adequately reinforced to resist any lateral force exerted by the torsion shaft and properly retain the shaft bearing in alignment with the torsion shaft.

9.3.5 Spring anchor plates shall be so designed as to adequately transmit torque from the stationary end of a torsion spring to the building structure and, at the same time, support the weight of the torsion shaft, multiplied by a safety factor of 2, in a level attitude. The anchor plate shall be able to withstand the lateral forces exerted by torsion spring.

9.3.6 Shaft bearings shall be of a type and design that adequately support the radial forces dictated by the weight of the counterbalance assembly and door weight, lateral forces exerted by the torsion shaft, and shall be able to tolerate minor shaft misalignment conditions.

9.4 Cable Assembly. The cable assembly that transmits door load shall be selected using a safety factor of 5. Cable shall be securely anchored at each end. Cable diameters shall not be greater than 5% of the diameter of the cable drum or cable sheave with which it will be used.

10. RESPONSIBILITIES OF OTHERS

10.1 Transmitted Loads

10.1.1 The track system shall be attached to the building at the points specified by the manufacturer ([Section 9.2.2](#)) using a method capable of supporting the door loads at each point. In addition, the supports shall resist twisting and swaying loads imposed on them by the track system.

10.1.2 The installation instructions shall advise that it is important that forces transmitted from an installed door system to the building structure be considered in the design of building openings for doors. These forces are evident at the building jambs when a door is subjected to wind pressure, at each spring anchor pad and its connection to the building header, and at all points where the horizontal track is attached to the building. Since these forces will vary, installation instructions shall specify that load information may be obtained by contacting the door system manufacturer.

10.1.3 The spring system shall be installed with fasteners supplied by the manufacturer, in accordance with the manufacturer's installation instructions.

11. DISCLAIMERS

11.1 Certification that a door system meets this standard does not constitute a warranty that the system will perform in accordance with the standards set forth in this standard, including but not limited to durability, thermal transmittance/air infiltration, or loads.

Certification implies only that the design of the listed door system, when tested in accordance with these standards (which may be random testing, if so specified), meets the applicable tests.

11.2 Many tests required by this standard are inherently hazardous and adequate safeguards for personnel and property must be employed in conducting such tests.

⇒ **END OF THE SPECIFICATION** ⇐

DASMA – the Door & Access Systems Manufacturers Association, International – is North America’s leading trade association of manufacturers of garage doors, rolling doors, garage door operators, vehicular gate operators, and access control products. With Association headquarters based in Cleveland, Ohio, our 90 member companies manufacture products sold in virtually every county in America, in every U.S. state, every Canadian province, and in more than 50 countries worldwide. DASMA members’ products represent more than 95% of the U.S. market for our industry.

For more information about the Door & Access Systems Manufacturers Association, International, contact:

DASMA

1300 Sumner Avenue
Cleveland, OH 44115-2851
Phn: 216/241-7333
Fax: 216/241-0105

E-Mail: dasma@dasma.com

URL: www.dasma.com